

DECLARATION OF PERFORMANCE



Saint-Gobain Building Glass Europe

Tour Saint-Gobain 12 place de l'Iris 92400 Courbevoie France

EN 1096-4 - Coated glass intended to be used in buildings and construction works

TIMELESS 6 mm M105725

NB: 0336, 0497, 0679, 0757, 0809, 1004, 1116, 1136, 1154, 1174, 1234, 1322, 1694, 1717, 1750, 1751

| ESSENTIAL CHARACTERISTICS | AVCP SYSTEMS | PERFORMANCES |
|---|--------------|--------------|
| For uses relating to safety in case of fire: | | |
| Resistance to fire | 1 | NPD |
| Reaction to fire | 3,4 | A1 |
| External fire performance | 3,4 | NPD |
| For uses as anti-bullet or anti-explosion glazing | | |
| Bullet resistance | 1 | NPD |
| Explosion resistance | 1 | NPD |
| For uses liable to present "safety-in-use" risks and subject to such regulations | | |
| Burglar resistance | 3 | NPD |
| Pendulum body impact resistance | 3 | NPD |
| Resistance against sudden temperature changes and temperature differentials (K) | 4 | 40 |
| Wind, snow, permanent and imposed load resistance (N/mm²) | 4 | 45 |
| For uses relating to noise reduction | | |
| Direct airborne sound insulation (dB) | 3 | 32(-1;-2) |
| For uses relating to energy conservation | | |
| Emissivity ⁸ a | 3 | 0.93 |
| U-value (W/(m².K)) | 3 | NPD |
| Light transmittance $^{	au_{_{\!$ | 3 | 0.89 |
| Light reflectance P√P', | 3 | 0.1/0.1 |
| Solar direct transmittance ${}^{	au}_{ullet}$ | 3 | 0.85 |
| Solar direct reflectance | 3 | 0.09/0.09 |
| g-value | 3 | 0.86 |
| Durability | 3 | А |
| F2=TIMELESS | | |

NPD: No Performance Determined

The performance of the product is in conformity with the declared performances. This declaration of performance is issued under the sole responsibility of the manufacturer. Signed for and on behalf of the manufacturer by:

Fabrice Desmons

03/10/2022

International Product Strategy Director Building Glass

Courbevoie - France

D-